

Digital Power Meter

E. TH343X TH344X series multi-channel digital power meter

Features

- Channel: 1/3/4
- AC/DC: Support AC and DC input test
- Soft start: using soft power switch design
- High-resolution display: 7 inches, 800×600 resolution, capacitive touch screen, support mouse operation
- Provide screenshot operation
- Broadband input: 0.1Hz-100kHz, suitable for most power systems on the market
- Embedded system: equipped with embedded operating system, the human-computer interaction is more flexible and friendly
- Comparison function: Provides 8 comparison channels for comparison output, and the output mode is programmable
- Harmonic analysis: analysis parameters are controllable, and list display and bar graph display are provided
- Waveform display: Provides basic input signal waveform display function and integrated power waveform display
- Vector display: Provide a vector display of the input signal
- Flexible energy integral control: provide continuous time control and manual control of energy integral run and stop operations
- File storage: a relatively powerful file system, compatible with most U disks (FAT format)
- Abundant interfaces: USB HOST, USB DEVICE, LAN, HANDLER, RS232/RS485 (choose one of two)
- Communication protocol: support SCPI command set and ModBus command parsing



Shelf volume: 215mm(W)x132mm(H)x441mm(D)
Dimensions: 236mm(W)x154mm(H)x475.5mm(D)
Net weight: 8.1kg

Standard ☒ RS232 ☒ USB HOST ☒ USB DEVICE ☒ LAN ☒

Option ☐ RS485 ☐

Application

- Motors, transformers
 - Electronic production design
 - Lighting
 - Aerospace and military industry
 - Network communication
 - Audio and video equipment
 - Monitoring equipment
 - Source class device
- Test and analysis of electrical parameters of AC power supply, DC power supply, linear power supply, switching power supply, and inverter and other source output equipment
- Load equipment
- Test and analysis of electrical parameters of various types of household appliances, industrial appliances, various electronic loads and other electrical equipment

Specifications

Model		TH3431	TH3433	TH3434	TH3441	TH3443	TH3444
Number Of Channels		1	3	4	1	3	4
Display		7-Inch (800x480) Color TFT Resistive Touch Screen					
Wiring Mode		One-Phase Two-Wire (1P2W)	One-Phase Two-Wire (1P2W)		One-Phase Two-Wire (1P2W)	One-Phase Two-Wire (1P2W)	
			One-Phase Three-Wire (1P3W)			One-Phase Three-Wire (1P3W)	
			Three-Phase Three-Wire (3P3W)			Three-Phase Three-Wire (3P3W)	
			Three-Phase Four-Wire (3P4W)			Three-Phase Four-Wire (3P4W)	
			Three-Voltage Three- Current (3V3A)			Three-Voltage Three- Current (3V3A)	
Basic Features	AC	Y			Y		
	DC	Y			Y		
	Precision Type	Y			Y		
	Micro Current	Y			Y		
	Harmonic Analysis	Y			Y		
	Electric Energy Test	Y			Y		
Display Mode	Data	Y			Y		
	Integration Data	Y			Y		
	Waveform Graph	Y			Y		
	Vector Analysis	Y			Y		
	Histogram	Y			Y		
Basic Accuracy (One Year)							
Voltage	Basic Accuracy	0.15% Reading + 0.2% Range					
	Resolution	0.001V					
Current	Basic Accuracy	± (0.15% Reading + 0.1% Range)					1mA
	Resolution	0.1mA					
Frequency Range		Voltage/Current Accuracy					
DC		± (0.1% Reading +0.2% Range)					
0.1Hz ≤ Freq < 45Hz		± (0.1% Reading +0.2% Range)					
45Hz ≤ Freq < 66Hz		± (0.1% Reading +0.1% Range)					

Digital Power Meter

E. TH343X TH344X series multi-channel digital power meter

Specifications

66Hz ≤ Freq < 1khz		± (0.1% Reading +0.2% Range)	
1khz ≤ Freq < 10khz		± ((0.07*Freq) % Reading +0.3% Range)	
10khz ≤ Freq ≤ 100khz		± (0.5% Reading +0.5% Range) ± [0.04*(Freq - 10k)] % Reading	
Input			
Voltage	Scope	1V - 600V	
	Range	15V/30V/60V/150V/300V/600V	
	Minimum Resolution	0.001V	
	Input Impedance	2M Ω	
	Allowed Max Input	1000V (1S) 700V(Continuous)	
Current	Scope	0.01mA - 2A	0.1mA - 20A
	Range	0.5mA/1mA/2mA/5mA/10mA/20mA	5mA/10mA/20mA/50mA/100mA/200mA
	Input Impedance	4 Ω	400m Ω
	Range	0.05A/0.1A/0.2A/0.5A/1A/2A	0.5A/1A/2A/5A/10A/20A
	Input Impedance	40m Ω	4m Ω
	Minimum Resolution	0.1uA	1uA
	Allowed Max Input	3A(1S) 2A(Continuous)	30A(1S) 20A(Continuous)
Power	Range	0.01mW - 1.2kW	0.1mW - 12kW
	Minimum Resolution	0.001mW	0.01mW
Frequency	Range	Fundamental Frequency Range: DC/0.1Hz - 100kHz, Filter 500Hz	
	Minimum Resolution	0.01Hz	
Power Factor	Range	- 1.000 - 1.000	
	Minimum Resolution	0.001	
Harmonic Analysis	Range	10Hz-1.2kHz	
	Accuracy	± (5% Reading +0.3% Range)	
Energy Integration	Range	0 - 99999kWh	
	Resolution	0.001Wh	
	Accuracy	± (0.2% Reading +0.3% Range)	
Energy Timing	Range	0 - 9999: 59: 59	
	Resolution	1s	
	Accuracy	± 0.05%	
Update Rate		Optional 0.1s/0.25s/0.5s/1s/2s/10s/20s	
Lock Function		Data Lock	
Range Method		Auto/Manual	
Input Impedance		≥ 2M Ω (Voltage Input)	
Comparator		Over-Limit Sound And Light Alarm	
Output		8 Channel Programmable Relay Output	
Measurement Assistance Function			
Data Buffer Storage Function		The Test Results Are Stored In A U Disk, And Statistical Analysis Can Be Performed On The PC Side	
Save/Load Function		The Saving Of Setting Data Is Divided Into Measurement Parameter Setting And System Parameter Setting	
Keyboard Lock Function		Front Panel Keys And Touch Screen Operations Can Be Locked To Effectively Prevent Misoperation	
Communication Interface	Serial Communication	RS232C/RS485 Optional	
	USB HOST	Universal Serial Bus Socket, Type A; FAT16/FAT32 Format. U Disk Storage Or Designated Wireless Network Card (WIFI Supports RTL8192 And MT7601) And Other Equipment Support	
	USB DEVICE	Universal Serial Bus Socket, Small Type B (4 Contact Positions); Compatible With USBTMC - USB488 And USB2.0, Female Connector For Connecting External Controllers. Optional CDC Mode Or TMC Mode.	
	LAN	10/100baset Ethernet, 8 Pins, Stable Communication.	
	HANDLER	8 Channel Programmable Relay Output	
Storage		USB Waveform, Setting File	
Power Supply		AC220V± 10%, 50/60Hz± 5%, Soft Power Switch	
Size W*H*D	Working Size	236mm*154mm*475.5mm	
	Shelf Size	215mm*132mm*441mm	
Weight		8.1kg	